

All-round productivity at its best

The ECOSYS MA4500fx represents the perfect blend of output quality, priceless reliability, and data security. This device transforms workflows while keeping energy usage to a minimum, and its robustness and versatility makes it the ideal choice for workspaces that seek to do more with less.



ECOSYS MA4500fx

Monochrome MFP for A4 format

Up to 45 pages per minute in A4

Duplex printing and scanning



Specifications

GENERAL

KYOCERA ECOSYS Laser Monochrome Multifunctional
Operation panel: 21 characters x 5 lines (With back-light)
Type: Desktop
Engine speed: Up to 45 pages A4 per minute;
Duplex print speed: 22.5 page per minute, A4
Duplex copy speed: 22.5 page per minute, A4
Resolution: 1200 x 1200 dpi (print); 600 x 600 dpi (scan/copy)
Recommended Average Print Volume: 20,000 pages per month.
Maximum Life: 900,000 pages or 5 years.
Scan Volume: max. 1,800 pages per month.
Warm-up time: Approx. 16 seconds or less.
Time to first print: Approx. 5.3 seconds or less.
Time to first copy: Approx. 6 or less (DP);
Approx. 7 or less (Platen).
CPU: ARM Cortex-A53 Dual core 1.4GHz.
Memory: Standard 1GB; Max. 3GB (optional).
Standard interfaces: USB 2.0 (Hi-Speed), 1 x USB Host Interface,
Gigabit Ethernet (10BaseT/100BaseTX/
1000BaseT), optional Wireless LAN (IEEE 802.11b/g/n),
1 x eKUIO slot for optional internal print server or
SSD hard disc, Slot for optional SD Card.
Integrated accounting: 100 department codes.
Dimensions (W x D x H): Without packaging:
475 x 476 x 575 mm (without protrusions);
475 x 476 x 575 mm (including protrusions);
With packaging: 607 x 570 x 695 mm
Weight: Without packaging: Approx. 22.8 kg (with bundled toner)
Approx. 22.3 kg (without bundled toner)
With packaging: 30 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
ECOSYS MA4500fx:
Printing: 594.1 W
Copying: 606 W
Ready mode: 55.9 W
Low power mode: 38.3 W
Sleep-mode: 0.6 W
Noise (sound pressure level: ISO 7779/ISO 9296):
Copying/Printing: 54 dB (A)
Stand-by: 30 dB (A)
Safety standards: TÜV/GS, CE
This unit is manufactured according to ISO 9001 quality standard
and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness
of max. 0.11 mm. Please use paper recommended by
KYOCERA under normal environmental conditions.
Input capacity: Multi-purpose tray: 100 sheets, 60 to 220 g/m², A4,
A5, A6, B5, B6, Letter, Legal, Folio, Custom
(70 x 140 to 216 x 356 mm), Banner paper up to 915 mm. Standard
universal paper cassette: 500 sheet, 60–120 g/m², A4, A5, B5,
Letter, Legal, Folio, Custom (140 x 210 to 216 x 356 mm). Max. input
capacity with options: 2,600 sheets.
Duplex: Standard duplex unit, 60 to 120 g/m², A4, A5, B5, Letter,
Legal, Custom (140x 210 mm - 216 x 356 mm).
Document Processor: Reverse Auto Document Processor
as standard, 75 sheets, 50–120 g/m², A4, A5, A6, B5,
Letter, Legal, Custom (105 x 148 to 216 x 356 mm).
Output capacity: Max. 250 sheets face down with paper full sensor.

PRINT FUNCTIONS

Controller language: PRESCRIBE
Emulations: PCL6 (Sc/XL), KPDL3 (PostScript 3 compatible),
PDF Direct Print, XPS Direct Print, AES support, TIFF/JPEG
Direct Print Support, Open XPS, URF, PWG Raster,
PCLm, Line Printer, IBM Proprinter, Epson LQ-850.
Operating systems: All current Windows operating
systems, MAC OS X Version 10.9 or higher, Chrome OS, Linux, as
well as other operating systems on request.
Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4
fonts (Cambria), 1 Bitmap font, 45 types of one-dimensional
barcodes, 1 type of two-dimensional barcode (PDF417).
Print features: PDF Direct Print, Internet printing IPP 1.0,
E-mail printing, WSD print, secure printing IPP over TLS, Local and
network authentication, Network data encryption IPsec, HTTPS,
LDAP over TLS, SNMPv3, SMTP over TLS, POP over
TLS, Encrypted PDF Direct Print, TLS 1.3, Secure Boot, Run-time
Integrity Check, Universal Print, Printing for Chrome OS.
Mobile printing support: KYOCERA Mobile
Print app for iOS and Android, AirPrint, Mopria,
Microsoft Universal Print, Wi-Fi Direct (Opt).

COPY FUNCTIONS

Max. original size: A4/Legal.
Continuous copying: 1–999.
Zoom range: 25–400% in 1% steps.
Preset magnification ratios: 7 Reductions / 5 Enlargements. **Image
adjustments:** Text + Photo, Photo, Text, Chart/Map, Printed
document.
Features: Electronic sort (collate), ID card copy, Zint, 4int, auto
cassette change, Skip blank page, Skip Line.

SCAN FUNCTIONS

Functionality: Scan-to-E-mail, Scan-to-FTP, Scan-to-SMB, Scan to
USB Host, Network TWAIN, WIA, WSD scan, Chrome OS (Scan),
AirPrint, Mopria.
Scan speed Simplex: 60 ipm (300 dpi, A4, b/w);
40 ipm (300 dpi, A4 colour)
Scan speed Duplex: 26 ipm (300dpi, A4, b/w);
17 ipm (300 dpi, A4, colour)
Scan resolution: 600, 400, 300, 200 dpi; 256 greyscales per colour
Max. scan size: A4, Legal, Banner paper (max 915mm).
Original recognition: Text, photo, text + photo, light text
File types: TIFF/JPEG, XPS, Open XPS, PDF, PDF/A, PDF/A-
1a/b, PDF/A-2a/b/u, Encrypted PDF, High compression PDF.
Compression method: MMR/JPEG
Features: Banner Scan, Colour scan, integrated address book,
Active Directory support, encrypted data transfer, multi send
(e-mail, fax, SMB/FTP folder, print) at once, Blank page skip.

FAX FUNCTIONS

Compatibility: Super G3.
Modern speed: Max. 33.6 kbps.
Transmission speed: Max. 3 seconds (JBIG).
Scanning speed: 2.0 seconds or less.
Address book: 200 entries
Scanning density:
Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi)
Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi)
Superfine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi)
Ultrafine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi)
Halftone: 256 grey scales
Maximum original size: A4/Legal, Banner (max 915mm)
Compression method: JBIG, MMR, MR, MH.

Memory reception: 256 sheets or more.

Features: Network fax, duplex transmission and
reception, encrypted transmission and reception,
polling transmission and reception, broadcast.

CONSUMABLES

Average continuous toner yield in accordance with
ISO/IEC 19752.
TK-3404 Toner Kit:
Microfine toner black for 12,500 pages A4.
Capacity of starter toner is 6,000 pages A4.

OPTIONS

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets,
60 - 120 g/m²; A4, A5, B5, Letter, Legal,
Custom (92 x 162 mm - 216 x 356 mm)
CB-360W-B Cabinet: Wooden desk with storage
capacity, Approx. 380 x 411 x 508 mm (WxDxH)
CB-365W-B Cabinet: Wooden desk with storage
capacity, Approx. 380 x 411 x 254 mm (WxDxH)
CA-3100 Caster Unit: for increased stability. Mandatory
when installing 4 optional paper feeders.
Memory upgrade: MM-21(2GB)/MM-20(1GB)
Storage Devices for easy document management:
HD-17 SSD hard disk: 64GB
HD-18 SSD hard disk: 256GB
HD-19 SSD hard disk: 512GB

SECURITY OPTIONS

Data Security Standard
UG-33 AC: ThinPrint support
UG-50: TPM (Trusted Platform Module)
USB IC Card Reader + Card Authentication Kit (B):
Support for various authentication keys available.
CRH 10: IC card Reader Holder.
Optional interface:
IB-37: Wireless LAN (802.11b/g/n, 2.4-GHz and 5-GHz)
with Wi-Fi Direct
IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/1,000 BaseT
IB-51: Wireless LAN Interface (802.11b/g/n)

WARRANTY

2-years on-site as standard.

WHAT'S IN THE BOX:

Main unit, starter toner, waste toner box, Quick guide, Safety
Guide, Operation panel sheet, power supply cord.

ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their
long-life components, ECOSYS devices are designed to maximise durability
and minimise the total cost of ownership with regard to maintenance,
administration and consumables. The cartridge-free system means that only
the toner has to be replaced regularly. The modular design concept allows
you to add workflowenhancing functions as required. Integrated system
software provides long-term crossnetwork compatibility. KYOCERA's long-
life components cost you and the environment less.



KYOCERA Document Solutions Partner

APRIL2023ECOSYSMA4500fx/VER1.0

KYOCERA Document Solutions Australia

Ph: 13 59 62

www.kyoceradocumentsolutions.com.au

KYOCERA Document Solutions New Zealand

Ph: 0800 459 623

www.kyoceradocumentsolutions.co.nz

